

T E S T C E R T I F I C A T E

CT-20-12-15-02

Product group: Homapal-Metal-Laminate

Products: Homapal-Metal Laminate 442
Homapal-Metal Laminate 470
Homapal-Metal Laminate 490

Manufacturer: HOMAPAL GmbH
Bahnhofstraße 30/32
37412 Herzberg am Harz
Germany

Specification: German Chemical Prohibition Ordinance (ChemVerbotsV) Appendix 1 of §3 dated 2017-01-20 in connection with the "Bekanntmachung analytischer Verfahren..." published on 26 November 2018, BAnz AT 26.11.2018 B2

Test method: Chamber test method EN 717-1;
Chemical analysis method: Acetyl acetone method

Report: Test report 2520392/1; 2520392/2; 2520392/3 dated 15 December 2020

**Test results
and
Evaluation:**

Product	Formaldehyde release DIN EN 717-1			German ChemVerbotsV	
	Unit	Measured value	Measured value multiplied with Factor 2	Quality fulfilled	
				Yes	No
Homapal-Metal Laminate 442	ppm	< LOD	< LOD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	µg / m ³	< LOD	< LOD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Homapal-Metal Laminate 470	ppm	< LOD	< LOD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	µg / m ³	< LOD	< LOD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Homapal-Metal Laminate 490	ppm	< LOD	< LOD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	µg / m ³	< LOD	< LOD	<input checked="" type="checkbox"/>	<input type="checkbox"/>

LOD...Limit of detection 0.008 ppm

Dresden, 15 December 2020



Head of laboratory




Engineer in charge